

PRINT & PACKAGING PAPER

PROBARRIER Greaseproof Paper

KIT 1-3

KIT 4-6

KIT 7-9

Customized











DREWSEN SPEZIALPAPIERE – Your partner in the packaging sector

We offer you both standard and tailor-made solutions.

With our film press technology, we are able to produce high-quality barrier coatings on two paper machines.

The working widths (225 cm, 470 cm) offer a lot of interesting possibilities for the processing industry.

As a manufacturer of security paper, we are known in the industry as a company with high quality standards.

Consistent product properties are our strength.

Contact us for tailored services and storage solutions.

As a healthy family-run company you will find in us a long-term flexible partner at your side.



Product information

PROBARRIER Standard

KIT ranges:

KIT 1-3

KIT 4-6

KIT 7-9

substances:
34-160 g/m²

PROBARRIER Individual

Specially tailored solutions for your requirements and applications

- · customized KIT values
- special substances
- · individual colours
- · special surfaces

Properties

- oil and grease repellent on both sides
- improved wet strength
- colour natural white free of optical brighteners
- · high strength properties
- very good printability on both sides (flexo/offset printing)
- excellent running and processing properties
- consistently high product quality
- heat resistant up to 220°C on demand
- · tasteless and odourless
- pH-neutral, non-aging
- · manufactured from primary fibre
- · recyclable, compostable*

Applications

- flexible packaging for direct food contact
- paper bags/bags for baked goods and fast food
- wrapping paper for the catering and food industry (fish, meat, cheese, baked goods, etc.)
- · sandwich paper
- pastry cases, muffin cups
- · cake underlays/doilies
- microflute applications/ laminates for food packaging (biscuits, confectionery, fast food, etc.)

Certificates

- ISEGA certificates/food legislation conformity
 - Recommendation BfR XXXVI/1
 - Recommendation BfR XXXVI/2
 - FDA
 - EU 19/35/2004
 - DM 21/03/73
- FABES migration analysis
- PFOA- and PFOS-free (non-detect)
- ISO 9001, 14001
- FSC®/PEFC on request





Technical specifications

• machine widths: 225 cm, 470 cm

• reel widths: 16 cm to 234 cm

• reel diameter: 60 cm to 145 cm

· cores: 70, 76, 100, 120, 150 mm

· sheets: on request

Germany